TESY
It's impressive



AQUATHERMICA COMPACT

AQUATHERMICA COMPACT 150



TIN	305969
Kapacita	143 L
Rozsah	143
Výška	1682 m
Chladivo	R513 a
Energetická trieda	A+
Maximum working pressure	8 bar
Height	1682 mm

Priemer	541 mm
Heating time	9:08 h:min
Declared load profile	L
Electric heating element power	1.5 kW
Min. ÷ max temperature heat pump air intake (90% R.H.)	-5 ÷ 43 °C
Frequency	50 Hz
Annual electricity consumption in kWh under average climate conditions	884.2 kWh
Power supply	1/N/220-240 V
Compressor	Rotary
Min. ÷ max teplota v místě instalace	4 ÷ 40 °C
Ochrana kompresora	Thermal circuit breaker with automatic reset
Average consumption	0.239 kW
Ventilátor	Centrifugal
Ochrana motora	Internal thermal circuit breaker with automatic reset
Kondenzátor	Wrapped externally not in contact with water
Prepravná hmotnosť	82 kg
CoP (DHW)	3.4
Chladivo	R513a
Náplň chladiva	760
Ekvivalent CO2 (CO2e)	0.480
Objem zmiešanej vody pri 40° / V40 (EN 16147:2017 - A7/W55)	178 L
Average heat pump consumption [Condition EN16147:2017 A7/W55]	0.239 kW

Výška	1682 mm